



**Arizona Department of Transportation**  
**Intermodal Transportation Division**

206 South Seventeenth Avenue Phoenix, Arizona 85007-3213

Janice K. Brewer  
*Governor*

John S. Halikowski  
*Director*

June 10, 2011

Floyd Roehrich Jr.  
*State Engineer*

**TO: ALL ADOT Consultants and Drainage Designers**

**THRU: ADOT Engineering Consultants Services**

**RE: Drainage Design - Pavement Drainage n-values**

This communiqué overrides a previous announcement on this subject that was issued in an email on 8/3/2010, but which reached only a small number of consultants. It addresses pavement drainage analysis in the instances where 1 inch of AR-ACFC overlay is present in the cross-section, as commonly encountered on various freeway capacity improvement projects. We are requiring that the concrete n-value = .013 occurring within 4 ft of the curb and gutter should not be ignored. The rest of the cross-section n = .016. This means that within the 4 feet the reduced n-value should be accounted for accordingly in calculations.

If modeled as above we are finding that we are reducing the number of needed catch basins in total. I think we should get more detail with the analysis and derive greater benefits to save on cost and aesthetics.

Obviously this cannot be achieved by using the formula that incorporates a constant n-value for the entire cross-section; therefore other formulas have to be derived for this application.

Please feel free to contact the Drainage Office with any questions you may have

**Ken Akoh-Arrey, PE**

*Chief Drainage Engineer, Manager*

*Arizona Dept. of Transportation*

*Roadway Engineering Group*

*205 S. 17th Ave. Phoenix, AZ 85007, MD 634E*

*Tel (602) 712-8660*

*Fax (602) 712-3161*